

Tehnički list za artikl: NLWXD009ML

Desing WX LED 230V AC/DC ,CPS , stropna

Ceiling surface mounting or optional chain rope or pendant mounting, 1h/3h/8h adjustable; pictograms with arrows left, down, up are already mounted, viewing distance: 90m





Tehnički podaci

Vrsta svjetiljke	Panik svjetiljka
VB/CPS	Za centralni panik sustav (CPS)
Funkcija	S nadzorom i kombiniranim pogonom
Izvedba/tip	Plastične svjetiljke
Dizajn	WX
Boja	bijela
Područje detekcije (m)	90
Izvor svjetla	HP-LED (3W)
Napon (V)	230V AC 50Hz ±20%; 230V DC ±20%
IP stupanj zaštite	IP40
Način montaže	Stropna nadgradna
Min. temperatura okoline (°C)	-20
Maks. temperatura okoline (°C)	40
AA Class E 8101	AA4
Neto masa (kg)	1,50

Dimensions (mm)

NLWX...



Tablica artikla

OPIS	KAT. BROJ
Desing WX LED 230V AC/DC ,CPS , stropna	
Ceiling surface mounting or optional chain rope or pendant mounting, 1h/3h/8h adjustable; pictograms with arrows left, down, upNLWXD009ML are already mounted, viewing distance: 90m	
Dodatni pribor	
Ovjes lanci komplet za svjetiljke tip WG/WX	NLWKO
Par cijevnih nosača 500mm, kromirani, montaža strop	NL1PV