

Tehnički list za artikl: NLWXD403SC

WX sigurnosna svj. LED, 1-3h, SC, 230V, IP65, stropna mont.

Ceiling surface mounting or optional chain rope or pendant mounting, 1h/3h/8h adjustable; pictograms with arrows left, down, up are already mounted, viewing distance: 90m, LiFePO₄ battery



Tehnički podaci



Neto duljina (mm)	500,00
Neto širina (mm)	500,00
Neto visina (mm)	500,00
Neto masa (kg)	1,50
Vrsta svjetiljke	Panik svjetiljka
VB/CPS	Sa vlastitom baterijom
Funkcija	Samokontrola
Izvedba/tip	Plastične svjetiljke
Dizajn	WX
Boja	RAL 9003 (bijela)
Piktogram	Pictograms with arrows left, bottom, right in accordance with ISO 7010 already affixed at the factory

Tehnički podaci - nastavak

Područje detekcije (m)	90
Izvor svjetla	LED (5W)
Naponsko područje (V)	230V AC 50Hz ±20%
Power maintained mode (W)	7
Power non-maintained mode (W)	2
Power max. (W)	8,20
Baterija (V/Ah)	2x 3,2V/1,6Ah LiFePO4
IP stupanj zaštite	IP40
Otpornost na udarce	≥ IK03
Način montaže	Stropna nadgradna
Min. temperatura okoline (°C)	-5
Maks. temperatura okoline (°C)	40
AA Klasa E 8101	AA4
Proizvođač	Schrack

Dimensions (mm)

NLWX...



Tablica artikla

OPIS	KAT. BROJ
WX sigurnosna svj. LED, 1-3h, SC, 230V, IP65, stropna mont. Ceiling surface mounting or optional chain rope or pendant mounting, 1h/3h/8h adjustable; pictograms with arrows left, down, up NLWXD403SC are already mounted, viewing distance: 90m, LiFePO4 battery	
Dodatni pribor	
Ovjes lanci komplet za svjetiljke tip WG/WX	NLWKO
Par cijevnih nosača 500mm, kromirani, montaža strop	NL1PV
Set 2 kom baterija LiFePO4 3,2V 1,6Ah - svjetiljke LEO i LPK LiFePO4 baterije, u skladu sa UN3480 - UN 3480 : Lithium-Ion batteries	NLAKKU3216
	NLTESTSC2
Zaštitni poklopac za testne tipke NLTEST2	NLTEST2COV