

Tehnički list za artikl: NLZAW003WB

Emerg.lum.ZA 4x0,5W HighPower LED 3h 230V AC WirelessConnect

Wall surface mounting, with LiFePO₄ battery, emergency luminaire for illuminating round surfaces, with Bluetooth communication, 170lm



Tehnički podaci

Neto duljina (mm)	315,00
Neto visina (mm)	140,00
Neto dubina (mm)	65,00
Neto masa (kg)	2,20
Vrsta svjetiljke	Sigurnosna svjetiljka
VB/CPS	Sa vlastitom baterijom
Funkcija	WirelessConnect
Izvedba/tip	Metalna zaštita od udara
Dizajn	ZA
Boja	bijela
Vrijeme autonomije (h)	3
Izvor svjetla	LED (2W)
Lumen	170

Tehnički podaci - nastavak

Naponsko područje (V)	230V AC 50Hz ±20%
Power maintained mode (W)	3,90
Power non-maintained mode (W)	1,50
Power max. (W)	5,30
Baterija (V/Ah)	3,2/3,3 LiFePO4
IP stupanj zaštite	IP65
Otpornost na udarce	IK08
Način montaže	Stropna
Min. temperatura okoline (°C)	-5
Maks. temperatura okoline (°C)	40
AA Klasa E 8101	AA4
Proizvođač	Schrack

Abmessungen (mm)



Bohrabstände (mm)



Podatkovna tablica: Emerg.lum.ZA 4x0,5W HighPower LED 3h 230V AC WirelessConnect

					
2,00	0,21	3,13	0,58	9,43	3,89
2,50	0,18	3,34	0,58	10,51	4,14
3,00	0,16	3,44	0,57	11,28	3,18
3,50	0,11	3,47	0,55	11,3	2,79
4,00	0,03	3,45	0,53	10,71	1,97

Tablica artikla

OPIS	KAT. BROJ
Emerg.lum.ZA 4x0,5W HighPower LED 3h 230V AC WirelessConnect	
Wall surface mounting, with LiFePO4 battery, emergency luminaire for illuminating round surfaces, with Bluetooth communication, 170lm	NLZAW003WB
Dodatni pribor	
Bat.3,2V 3Ah za LED svjet. sa vl. napajanjem ,KSC,KMB i ZAW	
LiFePO4 baterija, UN3480 - Li-Ion baterije, kompatibilne s aku 3,2V 3,3Ah	NLAKKU3230