

Tehnički list za artikl: NLZAW003WL

Sigurnosna svje. ZAW 230VAC, bat., 3h, bežična, autot., zidna

Zinc die-cast, white, IP65, -5° up to 40°C, 4 x HP LED 0,5W, with LiFePO4 battery, batteries inside the luminaire, central switching, wall mounting, 170lm, WirelessControl Professional type




Tehnički podaci

Neto duljina (mm)	315,00
Neto visina (mm)	140,00
Neto dubina (mm)	65,00
Neto masa (kg)	2,20
Vrsta svjetiljke	Sigurnosna svjetiljka
VB/CPS	Sa vlastitom baterijom
Funkcija	WirelessControl Professional
Izvedba/tip	Metalna zaštita od udara
Dizajn	ZA
Boja	bijela
Vrijeme autonomije (h)	3
Izvor svjetla	LED (2W)
Lumen	170
Naponsko područje (V)	230V AC 50Hz ±20%
Power maintained mode (W)	3,90
Power non-maintained mode (W)	1,50
Power max. (W)	5,30
Baterija (V/Ah)	3,2/3,0 LiFePO4
IP stupanj zaštite	IP65
Otpornost na udarce	IK08


Tehnički podaci - nastavak

Način montaže	Stropna
Min. temperatura okoline (°C)	-5
Maks. temperatura okoline (°C)	40
AA Klasa E 8101	AA4
Proizvođač	Schrack

Dimensions (mm)



Drilling distances (mm)



Abstandstabelle - Min. Beleuchtungsstärke auf der Mittellinie: 1lx - Wartungsfaktor 0,80

					
2,00	0,21	3,13	0,58	9,43	3,89
2,50	0,18	3,34	0,58	10,51	4,14
3,00	0,16	3,44	0,57	11,28	3,18
3,50	0,11	3,47	0,55	11,3	2,79
4,00	0,03	3,45	0,53	10,71	1,97

Tablica artikla

OPIS	KAT. BROJ
Sigurnosna svje. ZAW 230VAC, bat.,3h,bežična, autot., zidna Zinc die-cast, white, IP65, -5° up to 40°C, 4 x HP LED 0,5W, with LiFePO4 battery, batteries inside the luminaire, central switching, wall mounting, 170lm, WirelessControl Professional type	NLZAW003WL
Dodatni pribor	
Bat.3,2V 3Ah za LED svjet. sa vl. napajanjem ,KSC,KMB i ZAW LiFePO4 baterija, UN3480 - Li-Ion baterije, kompatibilne s aku 3,2V 3,3Ah	NLAKKU3230