

Tehnički list za artikl: SR3PDIEM07

PDU Essential Metered; 24xC13; 6xSchuko; 400V; 16A

Measurement per phase, incl. mounting bracket with screws



SCHRACK-Info

- PDU ESSENTIAL Metered
- Metering per Phase
- Input: 16A/400V | 11 kW
- Output: 24xC13 0° IEC Socket 6xCEE7/3 35° Socket
- split into three phases
- Supply cable: 3.0m | 2,5mm²
- with CEE 16A plug, red
- Integrated function for measuring current, voltage, reactive, apparent and active power, active energy, frequency and power factor
- Hot-swappable controller
- Integrated web server with web interface
- 2x 1Gbit/s Ethernet connection
- 1x USB-A port
- 2x Interface for sensors
- 2.0" TFT color display
- incl. mounting brackets

Tehnički podaci

Neto duljina (mm)	1.468,50
Neto širina (mm)	45,00
Neto visina (mm)	60,00
Neto masa (kg)	1,90
EAN	4057298233081
CIJENA	1.171,00
Min. temperatura okoline (°C)	-5
Maks. temperatura okoline (°C)	45
Nazivni napon	400V
IP stupanj zaštite	IP20
Tip proizvoda	Metered Essential
Broj utičnica	30
Outlet type	24 x IEC320 C13 und 6 x CEE7/3
Nazivna struja (A)	16
Phases per feed	3
Tip priključka	CEE 16 A red
Protokol	CLI IPv6 IPv4 DNS SMTPS SSH HTTP NTP DHCP SMTP HTTPS SNMP Trap Syslog SNMPv2/v3 Telnet
Način ugradnje	Bracket (L-shape)

OPIS	KAT. BROJ
PDU Essential Metered; 24xC13; 6xSchuko; 400V; 16A	
Measurement per phase, incl. mounting bracket with screws	SR3PDIEM07