

Tehnički list za artikl: SR3PDIPM01

# Napojna letva PRO metered, 16xC13, 4xC19, 230V, 16A

Mjerenje po fazi, uklj. montažni nosač s vijcima



## SCHRACK-Info

- PDU PRO Metered
- Metering per phase
- Input: 16 A / 230 V | 3,6 kW
- Supply cable: 3,0 m | 2,5 mm<sup>2</sup>
- mit CEE plug 16 A blue
- Output: 16 x C13 IEC Socket + 4 x C19 IEC Socket
- Integrated function for measuring current, voltage, reactive, apparent and active power, Reactive, apparent and active energy, frequency and power factor
- Hot-swappable controller and power supply unit
- Integrated web server with web interface 1x Gbit/s (PoE) and 1x 10/100Mbit/s Ethernet connection
- Interface for PDU network (up to 20 PDUs)
- 1x RJ45 interface for up to ten external sensors
- 1x USB-C port (USB 2.0)
- 2.4" TFT color display
- Incl. frames for color coding (blue, red)
- Incl. mounting brackets (L-shaped)
- Packed in cardboard box
- Length 1076 mm

## Tehnički podaci

|                                |                                                                                                                                                        |
|--------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|
| Neto duljina (mm)              | 1.076,00                                                                                                                                               |
| Neto širina (mm)               | 56,00                                                                                                                                                  |
| Neto visina (mm)               | 70,00                                                                                                                                                  |
| Neto masa (kg)                 | 3,00                                                                                                                                                   |
| EAN                            | 4057298202872                                                                                                                                          |
| CIJENA                         | 1.450,00                                                                                                                                               |
| Min. temperatura okoline (°C)  | 0                                                                                                                                                      |
| Maks. temperatura okoline (°C) | 50                                                                                                                                                     |
| Nazivni napon                  | 230V                                                                                                                                                   |
| IP stupanj zaštite             | IP20                                                                                                                                                   |
| Tip proizvoda                  | Metered                                                                                                                                                |
| Broj utičnica                  | 20                                                                                                                                                     |
| Outlet type                    | 16 x IEC320 C13 und 4 x IEC320 C19                                                                                                                     |
| Nazivna struja (A)             | 16                                                                                                                                                     |
| Phases per feed                | 1                                                                                                                                                      |
| Tip priključka                 | CEE 16 A blue                                                                                                                                          |
| Protokol                       | LDAP<br>IPv6<br>IPv4<br>DNS<br>SNMPv1<br>SSH<br>HTTP<br>SNMPv3<br>SNMPv2<br>NTP<br>SSH2<br>DHCP<br>ModBus /TCP<br>SMTP<br>HTTPS<br>SNMP Trap<br>Syslog |
| Način ugradnje                 | Bracket (L-shape)                                                                                                                                      |

| OPIS                                                | KAT. BROJ  |
|-----------------------------------------------------|------------|
| Napojna letva PRO metered, 16xC13, 4xC19, 230V, 16A | SR3PDIPM01 |
| Mjerenje po fazi, uklj. montažni nosač s vijcima    |            |