

Tehnički list za artikl: SR3PDIPP02

PDU PRO Metered+, 36xCombo Outlets (C13, C15, C19, C21), 400V, 16A

Mjerenje po utičnici, uklj. montažni nosač s vijcima



SCHRACK-Info

- PDU PRO Metered+
- Metering per socket
- Input: 16 A / 400 V | 11 kW
- Supply cable: 3,0 m | 2,5 mm²
- with CEE plug 16 A red
- Output: 36x Combo C13/C15/C19/C21
- Integrated function for measuring current, voltage, reactive, apparent and active power, Reactive, apparent and active energy, frequency and power factor
- Hot-swappable controller and power supply unit
- Integrated web server with web interface 1x Gbit/s (PoE) and 1x 10/100Mbit/s Ethernet connection
- Interface for PDU network (up to 20 PDUs)
- 1x RJ45 interface for up to ten external sensors
- 1x USB-C port (USB 2.0)
- 2.4" TFT color display
- Incl. frames for color coding (blue, red)
- Incl. mounting brackets (L-shaped) </>

Tehnički podaci

Neto duljina (mm)	1.568,70
Neto širina (mm)	56,00
Neto visina (mm)	71,00
EAN	4057298230318
CIJENA	3.542,00
Min. temperatura okoline (°C)	0
Maks. temperatura okoline (°C)	50
Nazivni napon	400V
IP stupanj zaštite	IP20
Tip proizvoda	Metered+
Broj utičnica	36
Outlet type	36 x Combo Socket (C13/C15/C19/C21)
Nazivna struja (A)	16
Phases per feed	3
Tip priključka	CEE 16 A red
Protokol	LDAP IPv6 IPv4 DNS SNMPv1 SSH HTTP SNMPv3 SNMPv2 NTP SSH2 DHCP ModBus /TCP SMTP HTTPS SNMP Trap Syslog
Način ugradnje	Bracket (L-shape)

OPIS	KAT. BROJ
PDU PRO Metered+, 36xCombo Outlets (C13,C15,C19,C21), 400V, 16A	SR3PDIPP02
Mjerenje po utičnici, uklj. montažni nosač s vijcima	