

Tehnički list za artikl: XC1609803-

DIGI-SAT 3040 koaks.75Ohm 1.02/4.6, 110dB, kl.A, PVC, Eca, 500m

trostruki omotač, bubanj 500m



SCHRACK info

To guarantee high-quality, noise-free transmission of the high frequencies (from approx. 950 to 2150 MHz) from the LNB via multiswitch and SAT wall outlet to the SAT receiver it is necessary to use high-grade coax cables. Our high-frequency cables owe their top quality to their top-of-the-line components, cutting-edge production technology and the number of their shielding layers.



Tehnički podaci

Klasa	Klasa A
Unutarnji vodič	1,02 CU
Promjer izolacije	4,60 Cell PE
Vanjski vodič	2x Aluminium polyester film
Pletenica	0,12 Al x 16 x 8
Pokrov pletenice (%)	80
Razina zaštite (dB)	110
Promjer (mm)	6,80
Vanjski omotač kabela	PVC

Tehnički podaci - nastavak

Klasifikacija prema normi EN50575	Eca
Boja plašta	white
Min. radijus savijanja (mm)	70
Nominalna težina (kg/km)	49
Impedancija (Ohm)	75 ± 3
Istosmjerni otpor pri 20° C (Ohm/100m)	2,20
Min. temperatura okoline (°C)	-5
Maks. temperatura okoline (°C)	70
Duljina/pakiranje	500m - bubanj
Kapacitet	52 ± 4 pF/m
Kategorija	Koaks
Oklop	3 x shielded
Plašt/omotač	PVC
Vanjski promjer (mm)	6,8
Boja	bijela

Tehnički podaci

Nominalno prigušenje:	
50 MHz	4.20dB / 100m
100 MHz	5.70dB / 100m
200 MHz	7.90dB / 100m
300 MHz	9.60dB / 100m
470 MHz	12.30dB / 100m
860 MHz	17.60dB / 100m
1000 MHz	19.40dB / 100m
1350 MHz	22.40dB / 100m
1750 MHz	26.90dB / 100m
2050 MHz	28.50dB / 100m
2250 MHz	29.80dB / 100m
2400 MHz	32.80dB / 100m
2500 MHz	33.30dB / 100m
Gubici zbog povratnog signala:	
5 - 1.000 MHz	more than 24dB
1.000 - 2.000 MHz	more than 22dB
2.000 - 3.000 MHz	more than 20dB

Tablica artikla

OPIS	KAT. BROJ
DIGI-SAT 3040 koaks.75Ohm 1.02/4.6, 110dB, kl.A, PVC, Eca, 500m trostruki omotač, bubanj 500m	XC1609803
Dodatni pribor	
SAT koaksijalni F-utikač, natisni za DIGI-SAT 3000, 3030, 3040, 3050	XC16004983
Nosač kabel bubnja pri odmatanju, nosivost do 250kg roler za kableske bubnjeve širine do 52cm	HTOOL00006
SAT koaksijalni alat za kompresiju F-utikača XC1600xxxx .	XC1600720
DIGI-SAT alat za skidanje izolac. koaks. kab. 6.6-6.8 i 11 mm .	XC1600710
SAT završna utičnica R/TV/SAT, klasa A, RAL9010 uključen okvir 80x80mm i N/Ž kućište, RAL9010	HSATD3M
SAT utič. kraj. 4x, radio/CATV/2xSAT, kl.A, okvir 80x80, 9010 uključen okvir 80x80mm i N/Ž kućište, RAL9010	HSATD4M
Utičnica završna 2-struka, 2dB, kl.A, okvir+kućište, RAL9010 uključen okvir 80x80mm i N/Ž kućište, RAL9010	HSBKD2M